

Road Signage Africa Road Marking Paint is a paint for marking lines, arrows, symbols, bays and zones on roads and other paved surfaces. It comes in water-based and solvent-based versions and is sold through Express Print, Rivonia, Sandton.

Typical uses

- Centre lines, edge lines, stop lines and arrows on roads and private roads
- Parking bays, disabled bays, loading zones and no-parking areas
- Driveways, estates, office parks, shopping centres and filling stations
- Warehouse floors, factory walkways and forklift zones
- School grounds, sports courts and playgrounds
- Kerbs and yellow or red no-stopping lines

Colours and pack sizes

Colours	Red, Yellow, White, Black, Blue
Pack sizes	5 L and 20 L
Types	Water-based and solvent-based
Finish	To be confirmed - ask us

Technical data

Figures for the water-based and solvent-based versions are being confirmed. Ask us for the current values before you plan a job.

Paint type / binder	To be confirmed - ask us
Solids by volume	To be confirmed - ask us
Density	To be confirmed - ask us
Spreading rate (theoretical)	To be confirmed - ask us
Recommended film thickness	To be confirmed - ask us
Touch dry	To be confirmed - ask us
Ready for traffic	To be confirmed - ask us
Recoat time	To be confirmed - ask us
Thinner / clean-up	To be confirmed - ask us
Application temperature range	To be confirmed - ask us
Flash point	To be confirmed - ask us
Shelf life (unopened)	To be confirmed - ask us
Standard / specification	To be confirmed - ask us

Surface preparation

- The surface must be clean, dry and sound. Remove dust, sand, oil, grease, loose material and flaking old paint.
- Sweep or blow the area clean just before painting. Wash oily patches with a suitable degreaser and let them dry.

- On new asphalt or concrete, follow the curing time given by the surface installer before marking.
- Mark out lines with chalk line or string and use masking tape or stencils for sharp edges.

Application

- Stir the paint well before use and keep stirring from time to time during the job.
- Apply by brush, roller or line-marking machine.
- Do not paint on damp surfaces, in rain or when rain is expected before the paint is dry.
- Keep traffic and people off the markings until the paint is fully dry.
- For a test, paint a small area first and check adhesion and drying on site.

Storage

- Store tins tightly closed, upright, in a cool, dry and well-ventilated place.
- Keep away from heat, sparks, open flames and direct sunlight.
- Keep out of reach of children.

Health and safety

- Read the label on the tin and the safety data sheet before use (available on request).
- Use in a well-ventilated area. Wear gloves and eye protection.
- If paint gets in the eyes, rinse with plenty of clean water and get medical advice.
- Do not pour leftover paint or wash water into drains. Dispose of empty tins responsibly.

Ordering and contact

Order online at expressprint.co.za/road-marking-paint, or contact Express Print for a quote on larger quantities. Collect from our shop, free delivery within 15 km, or courier anywhere in South Africa.

The information in this sheet is given in good faith as a general guide. Site conditions, surfaces and methods of application are outside our control, so test the product on site before full use. Road Signage Africa may update this sheet without notice; ask for the latest issue.